

2710H Series

Fuel Gas Coalescer Filter Element

Element Information

2710H

2

V

Media

Multiple layers of fiberglass and microglass

Support Layer

Epoxy coated wire mesh

Efficiency

Solid Removal Rating: 0.3 μ @ 99.75%

Liquid Removal Rating: 0.3 μ @ 99.9%

0.010 ppmw

End Cap Configuration

Double Open Ended

Dimensions & Weight

	ID	OD	Length	Weight
2 =	11"	15-3/4"	24-5/8"	35 lbs.
4 =	8-7/8"	12-1/2"	24-1/2"	39 lbs.
5 =	8-7/8"	12-1/2"	24-1/2"	39 lbs.
6 =	11"	15-3/4"	24-5/8"	35 lbs.
7 =	11"	17-3/4"	36-1/4"	47 lbs.
9 =	4-1/2"	7-3/4"	36-1/2"	24 lbs.

Gasket Material

V = Viton (Flat)

VO = Viton (O-ring)

Consult Factory



Construction

End Caps: Stainless Steel

Cores: Heavy gage stainless steel perforated sheet

Recommended Operating Conditions

Change out Differential Pressure: 15 PSID

Continuous Maximum Temp.: 400° F

Intermittent Maximum Temp.: 450° F